

JETBOOK 9600P

For more information, please visit
[HTTP://WWW.NNERVISIONPC.COM](http://www.nnervisionpc.com)



Intel® Centrino™ Technology

Unwire



Featuring Intel® New Centrino™ 533MHz Technology

- Intel® Pentium-M Processor 533MHz Front Side Bus
- Intel 802.11 Wireless LAN
- 15.4" WXGA TFT Display
- 1.25" thin and 6.4 lb
- 3-in-1 Card Reader (SD/MMC/MS)

JETBOOK 9600 Specifications

Dimension

- 360mm x 265mm x 32.2mm(front/rear)
- 35mm (inner)

Weight

- 2.87 Kg (6.4lb)
- 15.4" Panel + ODD (Combo) + Battery Pack (8-cell)

CPU

- Dothan 533/400FSB Up to 2.13GHz

Chipset

- Alviso GM for Dothan platform (Alviso-PM circuit is reserved)
- 533Mhz FSB supported

Memory

- DDR-2 333 with 256MB/512MB/1GB module
- 0 MB on board
- Upgradeable to 2GB Memory by two sets of 1GB SODIMM
- One channel design
- Easy install from bottom side

ODD

- Standard 12.7mm, 24X CD-RW/ DVD Combo drive (CD-RW: Read/24X, Write/24X, Re-write/24X; DVD: Read/8X)
- **Optional** 12.7mm, DVD Dual drive (DVD-R/RW Write 1X, DVD+R/RW Write 2X, CD-R Write 16X, CD-RW Write 8X)

HDD

- 9.5mm, 2.5" HDD support with 30/40GB/60/80GB (4200/5400/7200rpm)
- PCI Bus Master Enhanced IDE/Ultra DMA 33 support

Display

- Standard 15.4" WXGA(1280 x 800).

Audio

- REALTEK ALC250 AC97 Codec
- Microphone-in and headphone-out
- Support jack sense function
- Keyboard control
- Capable of playing CD while LCD panel is closed (BTO)

Video Chip

- Shared up to 128MB VGA

PCMCIA

- ENE 712 (included Card bus + Flashcard Reader controller)
- PC Card 95 supported with one type-II (No type-III support) Card sockets
- No ZV-Port support
- Power switch ENE CP2211
- Additional 1394 Phy VIA VT6301

Communication

- Modem: V.92/56K bps (US/Canada/UK/Germany/ French) ,V90/56K (For other countries) specification compliant and 14.4K bps Send/Receive Fax with MDC solution
- LAN: board 10/100M bps (Realtek 8100CL single chip),
- Wireless LAN 802.11b/g Mini-PCI interface.
- Wireless Lan 802.11a/g (Optional)
- Easy service from K/B opening for WLAN

Keyboard

- ENE 910 K/B controller
- US 87 Key; 12 function keys; 4 cursor keys
- Windows Keys; Application Key
- 19.05mm pitch, 2.5mm stroke, H=5.7mm

Pointing Device

- Touch Pad with two buttons & scroll up/down function

I/O ports

- USB 2.0 x 3 ports
- One VGA port, 15 pins
- Microphone-in
- Headphone-out jack x 1
- DC-in jack
- RJ-11 jack for 56Kbps V.92 Modem
- RJ-45 jack x 1
- Kensington lock
- TV-Out (S-Video) x1
- 1394 x 1
- 3-in-1 card reader for SD-host/MMC/MS
- External USB FDD

Controls

- Power button / Lid switch controlled by software
- Wireless Communication Switch for Wireless device

User Keys

- Switch key for selecting the CD-Playback functions, MP3 function and IOMP (MODE button)
- Control buttons for CD/MP3/IOMP functions Backward Forward Play / Pause Stop Mode (CD/MP3/IOMP) Volume up and down button
- Control buttons for Short-Cut key functions Internet Access Button Email button

Speaker

- Two stereo speakers 2W

AC Adapter

- Universal AC adapter. 90-264V AC, 47-63HZ
- 65W with 19V DC output
- Dimension: (Hipro) 108 mm x 45.5mm x 25.9mm (Lite-On) 106mm x 47mm x 28 mm
- Weight: (Hipro) TBD g, (Lite-On) TBD g
- 3 pin type for AC inlet and AC plug

Battery

- 8 cell LI-ION of 18650 size battery pack w/ 65WH (14.8V x 4400mAh) capacity- Smart Battery Compliant

Operating System

- Windows XP HOME, Windows XP Pro